Míele







Steam Heated



Years Warranty



HM 16-80 32.5 in. wide roller

Features

- Quick and uniform steam for perfect ironing results
- Space-saving storage: 0.2 ft storage space.
- Durable long-lasting roller cover
- Flexibly positioned heater plate for perfect rotary ironing performance
- Convenient return feed
- Variable roller speed
- Finger guard for ultimate safety
- Quick-heating aluminum heater plate



Perfect Laundry Finish

Uniform pressure over the entire working width guarantees a perfect laundry finish.



Quick-heating aluminum heater plate

The quick-heating aluminum heater plate ensures the ironer is ready to operate in the shortest time possible.



Space-saving storage

The appliance only needs 0.2 ft storage space.



Steam function

Powerful against creases: Quick and uniform steam for perfect ironing results.

Mat. No.	Model	Heat Type	Electrical	Finish
10238590	HM 16-80	Electric	208-240 V / 50-60 Hz / 1 Ph, 2 x 20 A	White

Míele

Heated Type (EL)	
Working width 32 tit/16 in. (830 mm) Heater plate material Aluminum Throughput at 20% residual moisture (kg/h) 13 Width 38 3/4 in. (985 mm) Depth 14 to/16 in. (380 mm) Height 37 3/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44 to/16 in. (1,120 mm) Shipping Depth 17 3/4 in. (450 mm) Shipping Height 22 to/16 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Heater plate material Aluminum Throughput at 20% residual moisture (kg/h) 13 Width 38 ³/4 in. (985 mm) Depth 14 ¹5/¹6 in. (380 mm) Height 37 ³/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44 ¹/¹6 in. (1,120 mm) Shipping Depth 17 ³/4 in. (450 mm) Shipping Height 22 ³/¹6 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Throughput at 20% residual moisture (kg/h) Width Depth 14 15/16 in. (985 mm) Height 37 3/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44 1/16 in. (1,120 mm) Shipping Depth 17 3/4 in. (450 mm) Shipping Height 22 7/16 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Width 38³/4 in. (985 mm) Depth 14¹5/16 in. (380 mm) Height 37³/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44¹/16 in. (1,120 mm) Shipping Depth 17³/4 in. (450 mm) Shipping Height 22³/16 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Depth 14 15/16 in. (380 mm) Height 37 3/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44 1/16 in. (1,120 mm) Shipping Depth 17 3/4 in. (450 mm) Shipping Height 22 7/16 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Depth 14 15/16 in. (380 mm) Height 37 3/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44 1/16 in. (1,120 mm) Shipping Depth 17 3/4 in. (450 mm) Shipping Height 22 7/16 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Height 37³/4 in. (959 mm) Weight 86 lbs. (39 kg) Shipping Width 44¹/¹6 in. (1,120 mm) Shipping Depth 17³/4 in. (450 mm) Shipping Height 22⁻/¹6 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Weight 86 lbs. (39 kg) Shipping Width 44 ^{1/16} in. (1,120 mm) Shipping Depth 17 ^{3/4} in. (450 mm) Shipping Height 22 ^{7/16} in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Shipping Width 44 ¹¹¹6 in. (1,120 mm) Shipping Depth 17 ³/4 in. (450 mm) Shipping Height 22 ⁻¹/¹6 in. (570 mm) Shipping Weight 100 lbs. (45 kg)	
Shipping Depth173/4 in. (450 mm)Shipping Height227/16 in. (570 mm)Shipping Weight100 lbs. (45 kg)	
Shipping Depth173/4 in. (450 mm)Shipping Height227/16 in. (570 mm)Shipping Weight100 lbs. (45 kg)	
Shipping Height227/16 in. (570 mm)Shipping Weight100 lbs. (45 kg)	
Shipping Weight 100 lbs. (45 kg)	
Minimum ironer speed, can be set in ft/min 2.0	
Minimum ironer speed, can be set in ft/min 2.0	
2.0	
Maximum ironer speed, can be set in ft/min 4.5	
Standard electrical connection 208-240 V / 50-60 Hz / 1 Ph	
Heating Power 2.9-3.8 kW	
Fuse 2 x 20 A	



5610 McAdam Road, Mississauga, Ontario L4Z 1P1 905.890.1220 • 800.387.9503 • Fax: 905.890.7039 email: harco@harcoco.com • www.harcoco.com

