PDR 908

18 lbs. / 8 kg





FEATURES

- Honeycomb drum
- M Touch Flex user interface (no buttons or dials)
- Intelligent dryers Gentle and uniform
- PerfectDry system residual moisture sensors
- Programmable controls 35 programs;
 5 customizable
- Axial airflow for perfect drying results
- Practical large-surface filter
- FragranceDos capable
- Stacked or Side-by-Side
- Heat Pump Dryer recognized as the Most Efficient of ENERGY STAR in 2022



PerfectDry System

The PerfectDry system consistently measures the residual moisture of the laundry, thereby achieving precise drying results - even when the water quality differs widely.



Honeycomb Drum

The Honeycomb drum's sculptured honeycomb structure creates an air cushion between the drum wall and the laundry, for perfect drying results and a perfect laundry finish.



Practical Large-Surface Filter

Ergonomic convenience: the filter is easy to remove and captures the fluff from several drying cycles easily.



Perfect Anti-Crease

The dryer tumbles the laundry at regular intervals after the end of a cycle, effectively preventing creasing.

Mat. No.	Model	Heat Type	Electrical	Finish
11204480	PDR 908 HP	Heat Pump	2 AC 208-240 V, 60 Hz	Lotus White
11204490	PDR 908 HP	Heat Pump	2 AC 208-240 V, 60 Hz	Stainless Steel
11204500	PDR 908 EL*	Electric	2 AC 208-240 V, 60 Hz	Lotus White
11204510	PDR 908 EL*	Electric	2 AC 208-240 V, 60 Hz	Stainless Steel

Miele

PDR 908

18 lbs. / 8 kg

Model	PDR 908	
Heated Option (EL, HP)	Heat Pump or Vented	
Finish	Front in Stainless Steel or Lotus White	
Load Size	18 lbs. (8 kg)	
Drum Capacity	4.59 cu.ft. / 130 liter	
Width	23 ^{13/16} in. (605 mm)	
Depth	28 ^{1/4} in. (717 mm)	
Height	33 ^{7/16} in. (850 mm)	
Height to the bottom of the door	9 ^{1/2} -9 ^{7/8} in. (241-251 mm)	
Door opening diameter	14 ^{9/16} in. (370 mm)	
Net Weight	114 lbs. (52 kg)	
Shipping Width	26 in. (660 mm)	
Shipping Depth	32 ^{1/4} in. (820 mm)	
Shipping Height	37 in. (940 mm)	
Shipping Gross Weight	126 lbs. (57 kg)	
Plug type	NEMA L6-30	
PDR 908 HP	2 AC 208-240 V, 60 Hz	
Heating Power	1.2 kW	
Fuse	2 x 30 A	
PDR 908 EL	2 AC 208-240 V, 60 Hz	
Heating Power	3,40-4,30 kW	



