

ENERGY ADVANTAGE™

# MULTI-LOAD SOFT-MOUNT WASHERS

MXS20PD, MXS25PD, MXS30PD, MXS40PD, MXS55PD, MXS65PD

## COIN MARKET

Introducing the new Maytag Commercial Laundry Energy Advantage™ Multi-Load Soft-Mount Washers, the next generation of multi-load washers built for the demands of today and tomorrow.



### Revenue-Generating Controls

- 48 revenue-generating wash cycle options increase profitability
- Multiple language options



### MAYTAG connect 360° Compatible

- Receive maintenance alerts, change pricing, track revenue wirelessly, and more
- Customers can receive a text when machine is available or their laundry is complete



### Faster Spin

- 400 G spin speed extracts more water resulting in faster dry times



### Better Energy and Cleaning Performance

- TurboWash™ System spray baffles and tumble patterns provide optimal water savings and cleaning



### USB Programmability

- Easy uploads and downloads of machine settings and software



### New Door Design

- Larger door opening and 180-degree door swing allows for easier loading and unloading
- Oversized ergonomic door knob for easy opening
- Durable integrated door hinges



Model MXS40PD shown.






WHAT'S INSIDE MATTERS™

Visit [maytagcommerciallaundry.com](http://maytagcommerciallaundry.com)

# ENERGY ADVANTAGE™ MULTI-LOAD SOFT-MOUNT WASHERS

## MXS20PD, MXS25PD, MXS30PD, MXS40PD, MXS55PD, MXS65PD

### COIN MARKET

| WASHER SPECIFICATIONS                            |  |  |  |   |   |   |
|--|---|---|---|---|---|---|
| MODEL  | MXS20PDATS  | MXS25PDATS  | MXS30PDATS  | MXS40PDATS                                  | MXS55PDATS                                  | MXS65PDATS                                  |
| <b>MOTOR</b>                                     |   |   |   |   |   |   |
| Inverter Drive                                   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| Variable Speed                                   | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| HP (kw)  | 1.0 (0.75)  | 1.5 (1.1)   | 2.0 (1.5)   | 3.0 (2.2)                                   | 4.0 (3.0)                                   | 4.0 (3.0)                                   |
| Voltage  | 208–240V<br>*Single-Phase or<br>Three-Phase                                       | 208–240V<br>*Single-Phase or<br>Three-Phase                                       | 208–240V<br>*Single-Phase or<br>Three-Phase                                       | 208–240V<br>*Single-Phase or<br>Three-Phase | 208–240V<br>*Single-Phase or<br>Three-Phase | 208–240V<br>*Single-Phase or<br>Three-Phase |
| <b>BREAKER SIZE—AMPS</b>                         | 15A   | 15A   | 20A   | 20A   | 20A   | 20A   |
| <b>SPEED</b>                                     |   |   |   |   |   |   |
| Extract Speed—Max rpm                            | 1165  | 1075  | 1075  | 980   | 980   | 915   |
| Extract Speed—Max g-force                        | 400   | 400   | 400   | 400   | 400   | 350   |
| <b>LIQUID SOAP SIGNALS</b>                       | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| <b>CONTROLS</b>                                  | Rev-Gen   | Rev-Gen   | Rev-Gen   | Rev-Gen                                     | Rev-Gen                                     | Rev-Gen                                     |
| <b>CONNECTIVITY</b>                              | Connect 360™<br>Compatible  | Connect 360°<br>Compatible  | Connect 360°<br>Compatible  | Connect 360°<br>Compatible                  | Connect 360°<br>Compatible                  | Connect 360°<br>Compatible                  |
| <b>USB PROGRAMMABILITY</b>                       | Yes   | Yes   | Yes   | Yes   | Yes   | Yes   |
| <b>WATER INLET/HOSE</b>                          |   |   |   |   |   |   |
| Water Inlet—in.                                  | BSP 3/4   | BSP 3/4   | BSP 3/4   | BSP 3/4                                     | BSP 3/4                                     | BSP 3/4                                     |
| Operating Pressure—psi /bar                      | 14.5–116/1–8  | 14.5–116/1–8  | 14.5–116/1–8  | 14.5–116/1–8                                | 14.5–116/1–8                                | 14.5–116/1–8                                |
| Drain Size Diameter—in. (mm)                     | 3 (76)  | 3 (76)  | 3 (76)  | 3 (76)                                      | 3 (76)                                      | 3 (76)                                      |
| <b>CAPACITY</b>                                  |   |   |   |   |   |   |
| Lbs. (kg)  | 20 (9)  | 25 (11)   | 30 (14)   | 40 (18)                                     | 55 (24)                                     | 65 (28)                                     |
| Cylinder Volume—cu. ft. (liters)                 | 2.65 (75)   | 3.71 (105)  | 4.77 (135)  | 6.36 (180)                                  | 8.48 (240)                                  | 9.89 (280)                                  |
| Cylinder Diameter—in. (mm)                       | 20.87 (530)   | 24.4 (620)  | 24.4 (620)  | 29.53 (750)                                 | 29.53 (750)                                 | 29.53 (750)                                 |
| Cylinder Depth—in. (mm)                          | 13.39 (340)   | 13.71 (348)   | 17.63 (448)   | 16.05 (408)                                 | 21.40 (544)                                 | 24.95 (634)                                 |
| <b>COLOR</b>                                     |   |   |   |   |   |   |
| Front Panel                                      | Stainless Steel   | Stainless Steel   | Stainless Steel   | Stainless Steel                             | Stainless Steel                             | Stainless Steel                             |
| Side Panels                                      | Dark Gray   | Dark Gray   | Dark Gray   | Dark Gray                                   | Dark Gray                                   | Dark Gray                                   |
| <b>APPROXIMATE WEIGHT</b>                        |   |   |   |   |   |   |
| Crated—lbs. (kg)                                 | 441 (200)   | 518 (235)   | 606 (275)   | 871 (395)                                   | 992 (450)                                   | 1135 (515)                                  |
| Uncrated—lbs. (kg)                               | 408 (185)   | 463 (210)   | 563 (255)   | 838 (380)                                   | 948 (430)                                   | 1092 (495)                                  |
| <b>DIMENSIONS</b>                                |   |   |   |   |   |   |
| Height—in. (mm)                                  | 44.83 (1139)  | 49.16 (1249)  | 49.16 (1249)  | 56.45 (1434)                                | 56.45 (1434)                                | 56.45 (1434)                                |
| Width—in. (mm)                                   | 27.95 (710)   | 31.29 (795)   | 31.29 (795)   | 38.18 (970)                                 | 38.18 (970)                                 | 38.18 (970)                                 |
| Depth Including Handle and Vent on Back—in. (mm) | 31.10 (790)   | 31.29 (795)   | 37.20 (945)   | 38.18 (970)                                 | 43.50 (1105)                                | 46.65 (1185)                                |
| Floor to Bottom of Door—in. (mm)                 | 13.74 (349)   | 13.46 (342)   | 13.46 (342)   | 18.77 (477)                                 | 18.77 (477)                                 | 18.77 (477)                                 |
| Floor to Drain Outlet Center—in. (mm)            | 3.46 (88)   | 3.46 (88)   | 3.46 (88)   | 4.27 (109)                                  | 4.27 (109)                                  | 4.27 (109)                                  |
| Side to Drain Outlet Center—in. (mm)             | 9.05 (230)  | 9.05 (230)  | 9.05 (230)  | 10.62 (270)                                 | 10.62 (270)                                 | 10.62 (270)                                 |
| Door Opening Diameter—in. (mm)                   | 12.99 (330)   | 16.14 (410)   | 16.14 (410)   | 18.11 (460)                                 | 18.11 (460)                                 | 18.11 (460)                                 |

\*Single-Phase is CSA-approved.  
See specific instructions for proper installation.  
Because of continuous product improvement, Maytag reserves the the right to change specifications without notice.



**Five-Year Limited Warranty on Parts (Parts Only—Labor Not Included).** For the first five years from the original date of purchase, when this commercial appliance is installed, operated and maintained according to the instructions attached to or furnished with the product, Maytag brand of Whirlpool Corporation (hereafter “Maytag”) will pay for factory-specified replacement parts to correct defects in materials or workmanship that existed when this commercial appliance was purchased. This limited warranty does not include labor.

**Sixth- Through Tenth-Year Limited Warranty (Certain Component Parts Only).** In the sixth through tenth years from the date of original purchase, when this commercial appliance is installed, operated, and maintained according to instructions attached to or furnished with the product, Maytag will pay for factory-specified replacement parts for the following components to correct non-cosmetic defects in materials or workmanship in the part that prevent function of the product and that existed when this commercial appliance was purchased. This is a limited 10-year warranty on the named parts only and does not include labor: outer shell, drum and shaft assembly, inner welded frame and bearings and seals. See complete warranty for details.